

DAKTRONICS ANNOUNCER'S INTERFACE SPECIFICATIONS



The Sportsound® push-to-talk Announcer's Interface provides a single-point location to control voice announcements. The rugged powder-coated steel housing ensures that the interface stands up to more than everyday wear and tear. This interface features one (1) balanced microphone output, one (1) balanced auxiliary input and one (1) headphone jack. The headphone jack is driven by the auxiliary input and volume control for it is located on the front of the unit. Dynamic microphone and professional headphones are included.

The interface includes two methods for controlling audio input from the microphone; holding the momentary button gives the user direct confirmation of a live microphone, or pressing the continuous button once turns the microphone on, and pressing it again switches the microphone off. There is also a LED indicator to confirm that the microphone is live.

DIMENSIONS	WEIGHT	POWER	CONSTRUCTION	COLOR
3.25" H x 5" W x 7.5" D (83 mm, 123 mm, 191 mm)	3 lbs. (1.4 kg)	120 VAC to 12 VDC wall pack transformer	Powder-coated steel	Black

Note: Dimensions shown exclude gooseneck and microphone.

OPTIONS

- One (1) Single-muff microphone headset

FOR ADDITIONAL INFORMATION

- Quick Start Guide: [DD2222104](#) (online)